



FILLING AND TESTING KIT HFP - 400 ... - H (HEAVY)

The HENNLICH filling and testing kit HFP - 400 ... - H is the robust construction site version of the standard HFP, in an extremely robust, waterproof and dustproof transport case. The case contains two filling hoses of 2.5 m and 4 m as standard. It is also possible to supply other hose lengths. In addition to two selectable analogue pressure gauges, it contains a high-precision digital pressure gauge. Included are all necessary adapters for all accumulator types including a 1/4" BSP adapter.

TYPE CODE

DIGITAL PRESSURE GAUGE PRESSURE RATING [bar]

400

Length of filling hose [mm]

2500 / 4000 / 8000 / 10000

E.g.: 25/40 corresponds to 2 filling hoses of 2.5 m and 4 m

Pressure ratings of the analogue pressure gauge [bar]

1 = 6 bar, 2 = 10 bar, 3 = 25 bar,

4 = 100 bar, 5 = 250 bar, 6 = 400 bar

E.g.: 056 1 pressure gauge 250 bar + 1 pressure gauge 400 bar

Heavy version

HFP - 400 - 25/40 - 056 - H



Connection adapters for foreign gas cylinders available (see adapters for nitrogen cylinders)

Figure shows design with digital pressure gauge up to 400 bar and adapter for gas valves

THE COMPLETE FILLING AND TESTING KIT INCLUDES:

- » 1. Filling and testing base device for connection M28x1.5 with hexagon socket
- » 2. Adapter HFP-A-1 for gas valves 7/8" - 14 UNF
- » 3. Adapter HFP-A-2 for gas valves 7/8" - 14 UNF 690 bar
- » 4. Adapter HFP-A-3 for gas valves 5/8" - 18 UNF
- » 5. Reducer for gas valve 8V1 - VG8 (pertains to 4.)
- » 6. Pressure gauge (2 pieces included, selectable display range)
- » 7. Protective cap for filling hose connection coupling
- » 8. Filling hose connection coupling for charging device
- » 9. Filling hose connection coupling on bottle side
- » 10. Knurled nut for screwing on the charging device
- » A. Hand wheel for actuation
- » B. Pressure discharge valve
- » 6 mm Allen key (for opening M28x1.5 gas valve)
- » Additional gas valve adapter for BSP 1/4" gas valve adapter

